## NSN 5930-01-273-9799

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-273-9799



**Body Style:** Bushing mounted Hazardous Locations/environmental Protection: Waterproof **Body Diameter:** 0.562 inches **Bushing Length:** Between 0.415 inches and 0.435 inches **Body Length:** 1.000 inches Actuator Length: 0.750 inches **Actuator Style:** Rectangular **Actuator Height:** 0.750 inches **Actuator Width:** 0.750 inches **Actuator Color:** Black single actuator Illuminated Actuator Color: Red single actuator **Actuator Inscription:** 8-, drop single actuator Maximum Voltage Rating In Volts: 28.0 dc **End Application:** Sonar set an/sqs-56 Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc

## NSN 5930-01-273-9799

Push Switch - Page 2 of 2



**Precious Material And Location:** 

Contacts gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug and 3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0