

View Online at <https://aerobasegroup.com/nsn/5930-01-274-1007>

**Hazardous Locations/environmental Protection:**

Shock proof

**Overall Length:**

9.900 inches

**Overall Height:**

4.800 inches

**Overall Width:**

5.000 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches single mounting facility

**Individual Section Quantity:**

6

**Knob Manufacturer Code:**

27192

**Knob Manufacturer Part Number:**

A53-902

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.500 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Base single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and cam actuated and legend plate

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

4.0 amperes inductive load lowest ac voltage rating at sea level

**Special Features:**

Legend plate reads fwd, fast, slow, off, slow, fast

**Style Designator:**

In-line, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A052b0