Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-274-1007

Hazardous Locations/environmental Protection:
Shock proof
Overall Length:
9.900 inches
Overall Height:
4.800 inches
Overall Width:
5.000 inches
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
6
Knob Manufacturer Code:
27192
Knob Manufacturer Part Number:
A53-902
Longest Horizontal Distance Between Mounting Centers:
4.250 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.500 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Base single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and cam actuated and legend plate
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
7 single actuator
Terminal Type:
Tab w/screw
Contact Load Current Rating:
4.0 amperes inductive load lowest ac voltage rating at sea level
Special Features:
Legend plate reads fwd, fast, slow, off, slow, fast
Style Designator:
In-line, cam actuated

NSN 5930-01-274-1007

Rotary Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0

