## NSN 5930-01-274-4097

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-274-4097

	lala		/ · -!	F	Protection:
п	iazardous	Locations	/environiii	entai F	rotection:

Vibration resistant

**Overall Length:** 

Between 1.160 inches and 1.260 inches

**Overall Height:** 

0.521 inches

**Body Diameter:** 

0.560 mils and 0.640 centimeters

**Mounting Slot Width:** 

0.140 inches

**Body Height:** 

Between 0.350 inches and 0.405 inches

**Unthreaded Mounting Hole Diameter:** 

0.140 inches

**Distance Between Mounting Facility Centers:** 

0.937 inches

**Tempurature Sensing Element Type:** 

Internal sensor

**Operating Tempurature Rating:** 

Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit

**Mounting Method:** 

Bracket and slot and unthreaded hole

**Contact Action Stimulus:** 

Increase

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Tab, solder lug

**Contact Load Current Rating:** 

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 500.0 milliamperes lamp load second voltage

**Contact Adjustability:** 

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:** 

120.00 actuation point degrees fahrenheit and 95.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

## NSN 5930-01-274-4097

Thermostatic Switch - Page 2 of 2



O- 1	<b>D</b>	•	
Style	1 )69	ะเตท	ator.
CLYIC		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ato:

Disc w/flange

## **Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-s-24236/24 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0