NSN 5930-01-274-4101

Push Switch - Page 1 of 2

Test Data Document:



View Online at https://aerobasegroup.com/nsn/5930-01-274-4101

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
0.800 inches
Overall Height:
1.890 inches
Overall Width:
0.800 inches
Body Length:
0.745 inches
Body Width:
0.745 inches
Body Height:
1.400 inches
Actuator Length:
0.600 inches
Actuator Style:
Rectangular
Actuator Height:
0.130 inches
Actuator Width:
0.600 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Green single actuator
Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 3.000 amperes resistive ac
Special Features:
Light emitting diode provided

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5930-01-274-4101

Push Switch - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

3 quick disconnect, male

Specification Data:

81349-mil-s-22885/93 government specification

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0