NSN 5930-01-274-7882

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-274-7882
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
2.770 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.150 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.620 inches
Inclosure Type:
Uninclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, permanent internal jumpers, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 7.000 amperes resistive ac
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 turret

NSN 5930-01-274-7882

Push Switch - Page 2 of 2



Specification D	ata:
-----------------	------

81349-mil-s-22885/67 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0