

View Online at <https://aerobasegroup.com/nsn/5930-01-274-8937>

Hazardous Locations/environmental Protection:

Shock proof and watertight

Overall Length:

9.900 inches

Overall Height:

5.250 inches

Overall Width:

5.000 inches

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

4.250 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.800 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Terminal Type:

Screw

Contact Load Current Rating:

4.0 amperes inductive load lowest ac voltage rating at sea level

Special Features:

Legend corresponds with positions and reads from left to right as follows; fast, slow, pu hoist, off, pu payout, slow, slow

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0