

View Online at <https://aerobasegroup.com/nsn/5930-01-274-8937>

**Hazardous Locations/environmental Protection:**

Shock proof and watertight

**Overall Length:**

9.900 inches

**Overall Height:**

5.250 inches

**Overall Width:**

5.000 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches single mounting facility

**Individual Section Quantity:**

5

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.800 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Terminal Type:**

Screw

**Contact Load Current Rating:**

4.0 amperes inductive load lowest ac voltage rating at sea level

**Special Features:**

Legend corresponds with positions and reads from left to right as follows; fast, slow, pu hoist, off, pu payout, slow, slow

**Style Designator:**

In-line, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0