NSN 5930-01-274-8942

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-274-8942

view Orilline at https://aerobasegroup.com/nish/3930-01-274-0942
Thread Class:
2b single mounting facility

Shock resistant and vibration resistant

Overall Length:

3.500 inches

Overall Height:

2.500 inches

Overall Width:

3.000 inches

Individual Section Quantity:

5

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.156 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

28 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 dc at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level and 10.0 amperes inductive load dc at sea level

NSN 5930-01-274-8942

Rotary Switch - Page 2 of 2



Sty	le [)es	ign	ato	r:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0