NSN 5930-01-275-0666



Push Switch - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/5930-01-275-0666	
Body Style:	
Panel mounted	
Hazardous Locations/environmental Protection:	
Explosion proof and humidity resistant	
Overall Length:	
3.440 inches	
Overall Height:	
1.250 inches	
Overall Width:	
1.000 inches	
Body Width:	
0.768 inches	
Body Height:	
0.768 inches	
Case Material:	
Metal	
Actuator Length:	
Between 0.740 inches and 0.760 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
Between 0.270 inches and 0.310 inches	
Actuator Width:	
Between 0.990 inches and 1.010 inches	
Actuator Color:	
Black single actuator	
Illuminated Actuator Color:	
Black single actuator	
Actuator Inscription:	
Speed test single actuator	
Maximum Voltage Rating In Volts:	
28.0 dc	
Mounting Surface To Terminal End Distance:	
3.150 inches	

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and full display lens

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

NSN 5930-01-275-0666

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Letters illuminate on actuation; upper in red, lower in green

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0