# NSN 5930-01-275-0667

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-275-0667

## Body Style:

Panel mounted

## Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

## **Overall Length:**

3.440 inches

### **Overall Height:**

1.250 inches

### **Overall Width:**

1.000 inches

**Body Width:** 

#### 0.768 inches

Body Height:

#### 0.768 inches

**Case Material:** 

# Metal

Actuator Length:

Between 0.740 inches and 0.760 inches

Actuator Style:

### Rectangular

Actuator Height:

Between 0.270 inches and 0.310 inches

## Actuator Width:

Between 0.990 inches and 1.010 inches

## Actuator Color:

Black single actuator

#### **Illuminated Actuator Color:**

Black single actuator

## Actuator Inscription:

Reset single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

## Mounting Surface To Terminal End Distance:

3.150 inches

## Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

## **Features Provided:**

Actuator seal and full display lens

# Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

# NSN 5930-01-275-0667

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

## **Special Features:**

Letters illuminate on actuation; upper in red, lower in green

Precious Material And Location:

Contacts gold

# Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0