# NSN 5930-01-275-0669

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

**Body Style:**Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-01-275-0669

Explosion proof and humidity resistant
Overall Length:
3.440 inches
Overall Height:
1.250 inches
Overall Width:
1.000 inches
Body Width:
0.768 inches
Body Height:
0.768 inches
Case Material:
Metal
Actuator Length:
Between 0.740 inches and 0.760 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.270 inches and 0.310 inches
Actuator Width:
Between 0.990 inches and 1.010 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
Range 1 nm single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
3.150 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and full display lens
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit

# NSN 5930-01-275-0669

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

### **Special Features:**

Letters illuminate on actuation; upper in red, lower in green

**Precious Material And Location:** 

Contacts gold

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0