NSN 5930-01-275-0673

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length: 3.440 inches Overall Height: 0.1250 inches



View Online at https://aerobasegroup.com/nsn/5930-01-275-0673

Overall Width:
1.000 inches
Body Width:
0.768 inches
Body Height:
0.768 inches
Case Material:
Metal
Actuator Length:
Between 0.740 inches and 0.760 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.270 inches and 0.310 inches
Actuator Width:
Between 0.990 inches and 1.010 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
Range 16 nm single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
3.150 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and full display lens
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit

NSN 5930-01-275-0673

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Letters illuminate on actuation; upper in red, lower in green

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0