

View Online at <https://aerobasegroup.com/nsn/5930-01-275-0775>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

10.125 inches

**Overall Height:**

4.250 inches

**Overall Width:**

5.000 inches

**Mounting Slot Width:**

0.344 inches

**Body Length:**

8.000 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.750 inches

**Longest Vertical Distance Between Mounting Centers:**

8.625 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and slot

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

270.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+14.74/+164.70 actuation point pounds per square inch absolute and +14.74/+164.70 deactuation point pounds per square inch absolute

**Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level second voltage

**Pressure Connector Type:**

Swivel nut, compression, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0