NSN 5930-01-275-0776

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-275-0776

Hazardous Locations/environmental Protection:

Dustproof and salt spray resistant and vibration resistant

Overall Length:

1.217 inches

Overall Height:

0.638 inches

Body Diameter:

0.640 inches

Mounting Slot Width:

0.140 inches

Body Height:

0.364 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Mounting Facility Centers:

0.937 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Bracket and slot and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

70.00 actuation point degrees fahrenheit and 60.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

NSN 5930-01-275-0776

Thermostatic Switch - Page 2 of 2



Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0