

View Online at <https://aerobasegroup.com/nsn/5930-01-275-0777>

Thread Class:

2b single mounting facility

Overall Length:

10.280 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Individual Section Quantity:

15

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

12 each section periphery

Mounting Facility Circle Radius:

0.905 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks each section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Data:

81349-mil-s-21604/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0