

View Online at <https://aerobasegroup.com/nsn/5930-01-275-0778>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

0.937 inches

Overall Height:

2.071 inches

Overall Width:

0.531 inches

Bushing Length:

Between 0.684 inches and 0.746 inches

Body Length:

1.150 inches

Body Width:

Between 0.875 inches and 0.937 inches

Body Height:

Between 0.469 inches and 0.531 inches

Actuator Style:

Round

Actuator Diameter:

Between 1.400 inches and 1.600 inches

Actuator Height:

0.090 inches

Actuator Free Position Height:

0.901 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.438 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

96.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.030 pretravel inches and 0.090 overtravel inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0