NSN 5930-01-275-0778

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-275-0778 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length:** 0.937 inches **Overall Height:** 2.071 inches **Overall Width:** 0.531 inches **Bushing Length:** Between 0.684 inches and 0.746 inches **Body Length:** 1.150 inches **Body Width:** Between 0.875 inches and 0.937 inches **Body Height:** Between 0.469 inches and 0.531 inches **Actuator Style:** Round **Actuator Diameter:** Between 1.400 inches and 1.600 inches **Actuator Height:** 0.090 inches **Actuator Free Position Height:** 0.901 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Hermetically sealed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.438 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, both positions maintained single switch unit **Switch Release Force:** 16.0 ounces **Switch Actuating Force:**

96.0 ounces

NSN 5930-01-275-0778

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	Mov	ıρm	Δn	+
~	υιu	awı	IVIO	ven		ш.

Between 0.020 pretravel inches and 0.030 pretravel inches and 0.090 overtravel inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0