

View Online at <https://aerobasegroup.com/nsn/5930-01-275-6545>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.188 inches

Overall Height:

9.250 inches

Overall Width:

2.810 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.410 inches

Shortest Horizontal Distance Between Mounting Centers:

0.660 inches

Longest Vertical Distance Between Mounting Centers:

3.280 inches

Temperature Sensing Element Type:

Bulb

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

0.5 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+40.00/+65.00 actuation point degrees fahrenheit and +40.00/+65.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Stimulus Rating:

53.00 actuation point degrees fahrenheit and 48.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A048b0