# NSN 5930-01-275-7468

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-275-7468

### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Driptight and dustproof

#### **Overall Length:**

0.960 inches

#### **Overall Height:**

2.425 inches

#### **Overall Width:**

0.960 inches

#### **Body Length:**

0.680 inches

## **Body Width:**

0.680 inches

## Body Height:

\_\_\_\_\_\_

## 1.975 inches

Case Material:

Metal

#### Actuator Length:

0.960 inches

#### Actuator Style:

Rectangular

#### Actuator Height:

0.275 inches

## Actuator Width:

0.960 inches

#### Actuator Color:

White single actuator and white single actuator

#### Illuminated Actuator Color:

Blue single actuator and green single actuator

#### **Actuator Inscription:**

Self/test single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

4910-01-112-9655

### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

## **Features Provided:**

Actuator seal

# NSN 5930-01-275-7468

Push Switch - Page 2 of 2



## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes resistive ac

#### **Special Features:**

Lens is horizontally split

Precious Material And Location:

Terminal surfaces gold

## **Terminal Type And Quantity:**

9 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

#### **Demilitarization:**

Yes - demil/mli

#### Fiig:

A053a0