

View Online at <https://aerobasegroup.com/nsn/5930-01-275-8237>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

4.570 inches

Overall Height:

Between 0.970 inches and 1.030 inches

Overall Width:

Between 0.970 inches and 1.030 inches

Body Diameter:

Between 0.970 inches and 1.030 inches

Bushing Length:

Between 0.525 inches and 0.555 inches

Body Length:

2.555 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.020 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes motor dc

Precious Material And Location:

Contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0