

View Online at <https://aerobasegroup.com/nsn/5930-01-275-8237>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

4.570 inches

**Overall Height:**

Between 0.970 inches and 1.030 inches

**Overall Width:**

Between 0.970 inches and 1.030 inches

**Body Diameter:**

Between 0.970 inches and 1.030 inches

**Bushing Length:**

Between 0.525 inches and 0.555 inches

**Body Length:**

2.555 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.420 inches

**Actuator Height:**

1.020 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position locked in

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Holding solenoid

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes motor dc

**Precious Material And Location:**

Contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0