NSN 5930-01-275-8243

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-275-8243

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Moisture resistant and salt spray resistant
Overall Length:
1.780 inches
Overall Height:
0.437 inches
Overall Width:
0.688 inches
Body Width:
0.688 inches
Body Height:
0.437 inches
Case Material:
Metal
Actuator Length:
0.640 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.095 inches and 0.125 inches
Actuator Width:
0.279 inches
Actuator Color:
Yellow single actuator
Illuminated Actuator Color:
Yellow single actuator
Actuator Inscription:
Scns single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
1.670 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action single switch unit

NSN 5930-01-275-8243

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc

inductive dc and 2.500 amperes lamp dc
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

IVO

Fiig:

A053a0