

View Online at <https://aerobasegroup.com/nsn/5930-01-276-5487>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

Between 2.807 inches and 2.817 inches

Overall Height:

2.500 inches

Overall Width:

Between 1.886 inches and 1.896 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

1.636 inches single mounting facility and 1.646 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.636 inches single mounting facility and 1.646 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0