

View Online at <https://aerobasegroup.com/nsn/5930-01-276-5618>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Width:

Between 2.280 inches and 2.340 inches

Case Material:

Metal

Actuator Length:

Between 1.470 inches and 1.530 inches

Actuator Style:

Roller arm

Actuator Height:

1.375 inches

Actuator Roller Diameter:

Between 0.720 inches and 0.780 inches

Actuator Roller Width:

Between 0.220 inches and 0.228 inches

Housing Height:

Between 2.070 inches and 2.130 inches

Housing Length:

Between 4.920 inches and 4.980 inches

Housing Width:

Between 2.220 inches and 2.280 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 4.190 inches and 4.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Between 1.780 inches and 1.840 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary 1st switch unit

Switch Actuating Force:

Between 11.0 ounces and 12.0 ounces

Actuator Movement:

Between 17.0 pretravel degrees and 20.0 overtravel degrees and 35.0 overtravel degrees and 11.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 1.200 amperes resistive ac

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0