

View Online at <https://aerobasegroup.com/nsn/5930-01-276-5619>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Width:**

Between 2.280 inches and 2.340 inches

**Case Material:**

Metal

**Actuator Length:**

Between 1.470 inches and 1.530 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

0.513 inches

**Actuator Roller Diameter:**

Between 0.720 inches and 0.780 inches

**Actuator Roller Width:**

Between 0.220 inches and 0.228 inches

**Housing Height:**

Between 2.070 inches and 2.130 inches

**Housing Length:**

Between 4.920 inches and 4.980 inches

**Housing Width:**

Between 2.220 inches and 2.280 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

Between 4.190 inches and 4.250 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

Between 1.780 inches and 1.840 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 600.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary 2nd switch unit

**Switch Actuating Force:**

Between 11.0 ounces and 12.0 ounces

**Actuator Movement:**

Between 17.0 pretravel degrees and 20.0 overtravel degrees and 35.0 overtravel degrees and 11.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 1.200 amperes resistive ac

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0