# NSN 5930-01-276-6294

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-276-6294

## **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.096 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Actuator Length:

#### 0.740 inches

Actuator Style:

Rectangular

#### Actuator Height:

0.100 inches

## Actuator Width:

0.740 inches

## Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

White single actuator

#### **Actuator Inscription:**

Arf 1 single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

#### **End Application:**

5895-01-174-7384 indicator, status id-2343/tsq-105 (v)

#### Mounting Surface To Terminal End Distance:

2.996 inches

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

## Features Provided:

Full display lens and holding mechanism

## Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit

# NSN 5930-01-276-6294

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

## **Precious Material And Location:**

Contacts gold

## Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A053a0