

View Online at <https://aerobasegroup.com/nsn/5930-01-276-8100>

Body Style:

Bushing mount

Overall Length:

Between 0.615 inches and 0.625 inches

Overall Height:

1.535 inches

Overall Width:

Between 0.315 inches and 0.325 inches

Bushing Length:

Between 0.443 inches and 0.453 inches

Body Length:

Between 0.615 inches and 0.625 inches

Body Width:

Between 0.315 inches and 0.325 inches

Body Height:

Between 0.455 inches and 0.465 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

Between 0.135 inches and 0.145 inches

Actuator Height:

Between 0.442 inches and 0.452 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

End contacts and center contact and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0