

View Online at <https://aerobasegroup.com/nsn/5930-01-276-8100>

**Body Style:**

Bushing mount

**Overall Length:**

Between 0.615 inches and 0.625 inches

**Overall Height:**

1.535 inches

**Overall Width:**

Between 0.315 inches and 0.325 inches

**Bushing Length:**

Between 0.443 inches and 0.453 inches

**Body Length:**

Between 0.615 inches and 0.625 inches

**Body Width:**

Between 0.315 inches and 0.325 inches

**Body Height:**

Between 0.455 inches and 0.465 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.135 inches and 0.145 inches

**Actuator Height:**

Between 0.442 inches and 0.452 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

**Precious Material And Location:**

End contacts and center contact and terminal surfaces silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0