## NSN 5930-01-276-8792

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-276-8792

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
3.094 inches
Overall Height:
1.200 inches
Overall Width:
0.960 inches
Body Width:
0.960 inches
Body Height:
1.200 inches
Case Material:
Metal
Actuator Color:
Amber single actuator
Illuminated Actuator Color:
Amber single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
1.900 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel and flange
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac
Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

### **Specification Data:**

81349-mil-s-2285/87 government specification

#### Shelf Life:

NI/o

# NSN 5930-01-276-8792

Push Switch - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A053a0