NSN 5930-01-276-9954

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-276-9954

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Submersible
Actuator Length:
2.000 inches
Actuator Style:
Roller arm
Actuator Height:
1.060 inches
Actuator Roller Diameter:
2.250 inches
Actuator Roller Width:
0.500 inches
Housing Height:
3.940 inches
Housing Length:
7.500 inches
Housing Width:
3.560 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 6.500 inches
6.500 inches
6.500 inches Maximum Voltage Rating In Volts:
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type:
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement:
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage:
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 200.000 milliamperes inductive dc and 5.000 amperes inductive ac
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 200.000 milliamperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity:
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 200.000 milliamperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 screw
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 200.000 milliamperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 screw Shelf Life:
Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 200.000 milliamperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 screw Shelf Life: N/a
Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 200.000 milliamperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 screw Shelf Life: N/a
6.500 inches Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 200.000 milliamperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 screw Shelf Life: N/a Unit Of Measure:
Maximum Voltage Rating In Volts: 440.0 ac and 250.0 dc Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, double make, momentary action single switch unit Contact Load Current Rating At Maximum Rated Voltage: 200.000 milliamperes inductive dc and 5.000 amperes inductive ac Terminal Type And Quantity: 4 screw Shelf Life: N/a Unit Of Measure: Demilitarization: