

View Online at <https://aerobasegroup.com/nsn/5930-01-277-0678>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Explosion proof

Actuator Length:

3.500 inches

Actuator Style:

Roller arm

Actuator Height:

0.318 inches

Actuator Roller Diameter:

1.500 inches

Actuator Roller Width:

0.310 inches

Housing Height:

3.250 inches

Housing Length:

6.380 inches

Housing Width:

4.690 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

5.380 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

3.630 inches

Maximum Voltage Rating In Volts:

440.0 ac and 355.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Actuator Movement:

Between 35.0 pretravel degrees and 45.0 pretravel degrees and 15.0 overtravel degrees and 25.0 overtravel degrees and 30.0 differential degrees and 40.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 1.500 amperes resistive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0