

View Online at <https://aerobasegroup.com/nsn/5930-01-277-0678>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Explosion proof

**Actuator Length:**

3.500 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

0.318 inches

**Actuator Roller Diameter:**

1.500 inches

**Actuator Roller Width:**

0.310 inches

**Housing Height:**

3.250 inches

**Housing Length:**

6.380 inches

**Housing Width:**

4.690 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

5.380 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

3.630 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 355.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Actuator Movement:**

Between 35.0 pretravel degrees and 45.0 pretravel degrees and 15.0 overtravel degrees and 25.0 overtravel degrees and 30.0 differential degrees and 40.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

0.500 amperes resistive dc and 1.500 amperes resistive ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0