## NSN 5930-01-277-2902

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-277-2902

Th	read	CI	acc.
	ı <del>c</del> au	U	ass.

2b single mounting facility

**Hazardous Locations/environmental Protection:** 

Explosion proof

**Overall Length:** 

0.410 inches

**Overall Height:** 

1.695 inches

**Overall Width:** 

1.700 inches

**Distance Between Mounting Facility Centers:** 

1.437 inches single mounting facility

**Individual Section Quantity:** 

1

#### **Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

## **Actuator Type:**

Push button all actuators

## Thready Qty Per Inch (tpi):

56 single mounting facility

## Thread Size:

0.086 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

115.0 ac at sea level28.0 dc at sea level

## **Mounting Facility Pattern:**

Two position in-line single mounting facility

## **Switch Actuator Indexing Position Quantity:**

10 single actuator

#### **Terminal Type:**

Printed circuit

## **Contact Load Current Rating:**

125.0 milliamperes resistive load ac at sea level125.0 milliamperes resistive load dc at sea level

## **Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

## **Contact Arrangement Truth Table:**

Bcd, 1 pole - 10 positions single section

#### Color:

Black single bodyblack single indicator backgroundwhite single indicator marking

## **Precious Material And Location:**

Contact surfaces gold

## **Precious Material:**

Gold

# NSN 5930-01-277-2902

Code Indicating Wheel Switch - Page 2 of 2



Sty	le	De	si	qı	na	to	r:
,	_			J.			

Rectangular indicating

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A052b0