NSN 5930-01-277-3252

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-277-3252

Body Style:					
Bushing mount					
Hazardous Locations/environmental Protection:					
Dustproof					
Overall Length:					
0.850 inches					
Overall Height:					
1.331 inches					
Overall Width:					
0.500 inches					
Bushing Length:					
0.350 inches					
Body Length:					
0.850 inches					
Body Width:					
0.500 inches					
Body Height:					
0.475 inches					
Case Material:					
Plastic					
Actuator Style:					
Round					
•					
Round					
Round Actuator Diameter:					
Round Actuator Diameter: 0.115 inches					
Round Actuator Diameter: 0.115 inches Actuator Height:					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship:					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts:					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc Inclosure Type:					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed Mounting Method:					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi):					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 40					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 40 Thread Size:					
Round Actuator Diameter: 0.115 inches Actuator Height: 0.410 inches Actuator Position-action Relationship: Up position maintained and down position momentary Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Thready Qty Per Inch (tpi): 40 Thread Size: 0.250 inches					

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

NSN 5930-01-277-3252

Toggle Switch - Page 2 of 2



P	racions	Matarial	And	Location:
_	recious	wateriai	Allu	LOCALION.

Contact and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0