

View Online at <https://aerobasegroup.com/nsn/5930-01-277-3255>

**Body Style:**

Bushing mount

**Overall Length:**

Between 0.825 inches and 0.855 inches

**Overall Height:**

2.596 inches

**Overall Width:**

0.719 inches

**Bushing Length:**

Between 0.455 inches and 0.485 inches

**Body Length:**

Between 0.825 inches and 0.855 inches

**Body Width:**

Between 0.635 inches and 0.665 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.423 inches and 0.433 inches

**Actuator Height:**

1.165 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position locked in and out and center position no locking action

**Maximum Voltage Rating In Volts:**

56.0 dc

**Mounting Surface To Terminal End Distance:**

Between 0.916 inches and 0.976 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 printed circuit

**Specification Data:**

98230-0n370492-1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0