

View Online at <https://aerobasegroup.com/nsn/5930-01-277-3255>

Body Style:

Bushing mount

Overall Length:

Between 0.825 inches and 0.855 inches

Overall Height:

2.596 inches

Overall Width:

0.719 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

Between 0.825 inches and 0.855 inches

Body Width:

Between 0.635 inches and 0.665 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.423 inches and 0.433 inches

Actuator Height:

1.165 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in and out and center position no locking action

Maximum Voltage Rating In Volts:

56.0 dc

Mounting Surface To Terminal End Distance:

Between 0.916 inches and 0.976 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Specification Data:

98230-0n370492-1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0