

View Online at <https://aerobasegroup.com/nsn/5930-01-277-3262>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

Between 1.960 inches and 2.020 inches

**Overall Height:**

Between 0.590 inches and 0.650 inches

**Overall Width:**

Between 0.590 inches and 0.650 inches

**Body Diameter:**

Between 0.590 inches and 0.650 inches

**Bushing Length:**

Between 0.410 inches and 0.470 inches

**Body Length:**

Between 1.140 inches and 1.200 inches

**Actuator Diameter:**

Between 0.350 inches and 0.410 inches

**Actuator Height:**

Between 0.250 inches and 0.310 inches

**Maximum Voltage Rating In Volts:**

5.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 milliamperes resistive dc

**Precious Material And Location:**

Contact surfaces gold and contacts silver

**Unable To Decode:**

Unable to decode and unable to decode

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 pin

**Specification Data:**

98230-0n370493-1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0