

View Online at <https://aerobasegroup.com/nsn/5930-01-277-3262>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

Between 1.960 inches and 2.020 inches

Overall Height:

Between 0.590 inches and 0.650 inches

Overall Width:

Between 0.590 inches and 0.650 inches

Body Diameter:

Between 0.590 inches and 0.650 inches

Bushing Length:

Between 0.410 inches and 0.470 inches

Body Length:

Between 1.140 inches and 1.200 inches

Actuator Diameter:

Between 0.350 inches and 0.410 inches

Actuator Height:

Between 0.250 inches and 0.310 inches

Maximum Voltage Rating In Volts:

5.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 milliamperes resistive dc

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 pin

Specification Data:

98230-0n370493-1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0