NSN 5930-01-277-4463

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-277-4463

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
Between 1.070 inches and 1.090 inches
Overall Height:
3.120 inches
Overall Width:
Between 1.070 inches and 1.090 inches
Body Length:
0.688 inches
Body Width:
0.688 inches
Body Height:
2.850 inches
Case Material:
Metal
Actuator Length:
Between 0.807 inches and 0.817 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.260 inches and 0.280 inches
Actuator Width:
Between 0.807 inches and 0.817 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Blue single actuator and green single actuator
Actuator Inscription:
Self test, go single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

NSN 5930-01-277-4463

Push Switch - Page 2 of 2



Special Features:
Includes seal adapter
Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0