

View Online at <https://aerobasegroup.com/nsn/5930-01-277-4463>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

Between 1.070 inches and 1.090 inches

**Overall Height:**

3.120 inches

**Overall Width:**

Between 1.070 inches and 1.090 inches

**Body Length:**

0.688 inches

**Body Width:**

0.688 inches

**Body Height:**

2.850 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.807 inches and 0.817 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.260 inches and 0.280 inches

**Actuator Width:**

Between 0.807 inches and 0.817 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Blue single actuator and green single actuator

**Actuator Inscription:**

Self test, go single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

Includes seal adapter

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

3 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0