## NSN 5930-01-277-4463

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-277-4463

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
Between 1.070 inches and 1.090 inches
Overall Height:
3.120 inches
Overall Width:
Between 1.070 inches and 1.090 inches
Body Length:
0.688 inches
Body Width:
0.688 inches
Body Height:
2.850 inches
Case Material:
Metal
Actuator Length:
Between 0.807 inches and 0.817 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.260 inches and 0.280 inches
Actuator Width:
Between 0.807 inches and 0.817 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Blue single actuator and green single actuator
Actuator Inscription:
Self test, go single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

## NSN 5930-01-277-4463

Push Switch - Page 2 of 2



Special Features:
Includes seal adapter
<b>Precious Material And Location:</b>
Contacts gold
Terminal Type And Quantity:
3 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0