

View Online at <https://aerobasegroup.com/nsn/5930-01-277-4463>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

Between 1.070 inches and 1.090 inches

Overall Height:

3.120 inches

Overall Width:

Between 1.070 inches and 1.090 inches

Body Length:

0.688 inches

Body Width:

0.688 inches

Body Height:

2.850 inches

Case Material:

Metal

Actuator Length:

Between 0.807 inches and 0.817 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.260 inches and 0.280 inches

Actuator Width:

Between 0.807 inches and 0.817 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Blue single actuator and green single actuator

Actuator Inscription:

Self test, go single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Includes seal adapter

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0