NSN 5930-01-277-5247

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-277-5247

| Body Style: |
|---|
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 1.940 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Body Length: |
| 1.940 inches |
| Body Width: |
| 0.690 inches |
| Body Height: |
| 0.930 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.280 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac and 250.0 dc |
| End Application: |
| Wasp class Ihd. |
| Inclosure Type: |
| Fully enclosed |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| Between 13.0 ounces and 19.0 ounces |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 0.250 amperes resistive dc and 15.000 amperes resistive ac |
| Precious Material And Location: |

3 screw

Contacts silver

Terminal Type And Quantity:

NSN 5930-01-277-5247

Sensitive Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0