

View Online at <https://aerobasegroup.com/nsn/5930-01-277-6758>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

Between 0.910 inches and 0.930 inches

Overall Height:

3.120 inches

Overall Width:

Between 0.910 inches and 0.930 inches

Body Length:

0.688 inches

Body Width:

0.688 inches

Body Height:

2.446 inches

Case Material:

Metal

Actuator Length:

Between 0.730 inches and 0.750 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.260 inches and 0.280 inches

Actuator Width:

Between 0.730 inches and 0.750 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Black single actuator

Actuator Inscription:

Stand alone integ single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Led lamps; legend characters illuminate red

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

9 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0