NSN 5930-01-277-6806

Thermostatic Switch - Page 1 of 2

Disc



View Online at https://aerobasegroup.com/nsn/5930-01-277-6806

Thread Class:
2a single threaded stud
Thread Length:
0.187 inches single threaded stud
Overall Height:
0.867 inches
Body Height:
0.437 inches
Overall Diameter:
Between 0.540 inches and 0.640 inches
Tempurature Sensing Element Type:
Disc
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit
Mounting Method:
Threaded stud
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
32 single threaded stud
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches single threaded stud
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load third voltage and 2.5 amperes inductive load third voltage and 1.0 amperes lamp load third voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
185.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:

NSN 5930-01-277-6806

Thermostatic Switch - Page 2 of 2



Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Unc single threaded stud

Specification Data:

81349-mil-s-24236/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0