NSN 5930-01-277-6808



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-277-6808 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length:** 2.485 inches **Overall Height:** 0.750 inches **Overall Width:** 0.750 inches **Body Diameter:** 0.750 inches **Bushing Length:** 0.438 inches **Body Length:** 1.015 inches **Actuator Length:** 0.500 inches **Actuator Style:** Rectangular **Actuator Height:** 0.906 inches **Actuator Width:** 0.500 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** White single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 30.0 dc **End Application:** Aircraft, hercules c-130/c-130f/kc-130; support equipment c-130 aircraft **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing

Mounting Method:
Threaded bushing
Features Provided:
Holding mechanism
Thready Qty Per Inch (tpi):
32
Thread Size:
0.562 inches

NSN 5930-01-277-6808

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangeme	nt:
------------------------------	-----

4 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

Special Features:

Weapopn system essential

Thread Series Designator:

Un

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0