

View Online at <https://aerobasegroup.com/nsn/5930-01-277-8138>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.750 inches

**Overall Height:**

2.320 inches

**Overall Width:**

0.750 inches

**Body Length:**

0.688 inches

**Body Width:**

0.620 inches

**Body Height:**

2.240 inches

**Case Material:**

Metal

**Actuator Length:**

0.689 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.160 inches

**Actuator Width:**

0.689 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Yellow single actuator

**Actuator Inscription:**

Barred, decr single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.500 amperes lamp ac

**Special Features:**

Actuator inscription readable in direct sunlight

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

6 tab, solder lug and 6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0