## NSN 5930-01-277-8139

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-277-8139

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Dustproof and driptight
Overall Length:
0.750 inches
Overall Height:
2.320 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.620 inches
Body Height:
2.240 inches
Case Material:
Metal
Actuator Length:
0.689 inches
Actuator Style:
Rectangular
Actuator Height:
0.160 inches
Actuator Width:
0.689 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Yellow single actuator
Actuator Inscription:
Ag-4, incr single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

## NSN 5930-01-277-8139

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.500 amperes lamp ac

## **Special Features:**

Actuator inscription readable in direct sunlight

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

6 tab, solder lug and 6 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0