NSN 5930-01-277-9616

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-277-9616

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

3.520 inches

Overall Height:

1.740 inches

Overall Width:

2.120 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Legend plate

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

750.0 milliamperes inductive load highest ac voltage rating at sea level

NSN 5930-01-277-9616

Rotary Switch - Page 2 of 2



Special Features:
Legend plate reads dome; dark ship
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0